

THUNDERSTORM SLIDE IN UNIT

The
THUNDERSTORM SLIDE IN UNIT
is built for the rigors of the fire service with the
highest quality components to maximize the
integrity, durability, and life of the unit.



pictured with additional
features and options



- All stainless steel plumbing
- 24hp Honda engine
- Booster reel, 1" with manual rewind
- 100' 1" booster hose
- 3 piece stainless steel valves with NH thread and ball control handles
- Tank to pump line with valve control at panel
 - High Pressure: 2" valve
 - High Volume: 2.5" valve
- Expandable discharge manifold, stainless steel, with garden hose discharge/drain
 - High pressure has (1) 1.5" gate valves
 - High volume has a 2.5" x (2) 1.5" gated wye
- Heavy duty Guzzler hand primer with metal top
- 3 gal Fuel tank with copoly mounting bracket
- 2 1/2" inlet with cap
- 1" tank fill line
- Push/Pull control linkage for tank to pump valve
- One year warranty on the unit

DIMENSIONS

94" L x 48" W

250 gallon: 52" H

400 gallon: 66" H

300 gallon: 56" H

500 gallon: 74" H

*pictured with some additional options and upgrades
 *10-gallon foam cell with 8 x 8" fill tower optional



NEW!

Completely enclosed control panel with on/off start, low pressure protection override, vernier throttle, choke, liquid filled gauge, low oil light, & light shield with LED light



NEW- "HOT SWAP"

Field replaceable pump end technology



Weather proof electrical box & high pressure flexline plumbing with stainless steel couplings



stainless steel valves with ball control handles on a painted stainless steel manifold



powder coated pump base



removable top with sleek stainless steel bolts



booster hose bracket



3 gal fuel tank with copoly mounting bracket

STANDARD HIGH-PRESSURE PUMP

- 4-Stage Hotshot Pump Standard
- Honda engine
- Rotary & mechanical seals
- Centrifugal pump
- Sealed ball bearings
- Brass wear ring
- Stainless steel shaft
- Belt driven speed increaser for lower rpm's and higher pressure

HIGH VOLUME PUMP

- Aluminum alloy pump casing
- Bronze impeller
- Stainless steel shaft
- Mechanical shaft seal

HIGH PRESSURE/MID RANGE "HOT SWAP" FIELD REPLACEABLE PUMPS

4-STAGE 4087-100032

MAX PRESSURE: 440 PSI | MAX FLOW: 106 GPM

- 430 psi @ 10 gpm
- 415 psi @ 20 gpm
- 350 psi @ 65 gpm
- 250 psi @ 94 gpm
- 150 psi @ 105 gpm

MID RANGE 4087-100067

MAX PRESSURE: 200 PSI | MAX FLOW: 300 GPM

- 290 gpm @ 10 psi
- 275 gpm @ 50 psi
- 215 gpm @ 100 psi
- 112 gpm @ 150 psi
- 50 gpm @ 175 psi

ADDITIONAL OPTIONAL PUMPS & PERFORMANCE

2-STAGE

3266-HHP24H

- 325 psi @ 35 gpm
- 295 psi @ 50 gpm
- 200 psi @ 90 gpm
- 150 psi @ 120 gpm

HALE

3266-HAL30024H

- 380 gpm @ 25 psi
- 320 gpm @ 50 psi
- 240 gpm @ 75 psi
- 150 gpm @ 100 psi

DARLEY

3266-DAR24H

- 390 gpm @ 25 psi
- 300 gpm @ 70 psi
- 180 gpm @ 120 psi
- 95 gpm @ 150 psi

REPLACE YOUR ENTIRE PUMP IN MINUTES!

NEW! FIELD REPLACEABLE PUMP

The Thunderstorm Slide in Unit now comes plumbed ready for our exclusive "hot swap" quick change pump technology allowing users to quickly and easily field replace the Hot Shot 4 pump with minimal tools, because sometimes things happen. Purchase our optional pump end replacement kit and never be without a pump in the field.



Quick-release clamp & pump end



Wrenches for the grooved bolt-on coupling clamps

KIT INCLUDES:

- Hot Shot 4 or Hellcat X2 pump end with quick-release clamp & 2 grooved bolt-on coupling clamps
- (1) 8" adjustable wrench
- (1) 7/16" wrench
- (1) 11/16" wrench

Release the clamp, use the wrenches to remove the bolt-on couplings, and then replace pump end with a new one.

Standard TANK features

Engineered to withstand the rigors of the fire service, G3 Fire® MAGNITUDE copolymer polypropylene is UV stabilized with 10x the impact strength of standard polypropylene even through wide temperature ranges.

- 250 gallon, lightweight & corrosion resistant G3 Fire® MAGNITUDE copolymer polypropylene tank with limited lifetime warranty
- Full NFPA baffling
- Removable top for cleaning & service
- Built-in water sight gauge
- An internal sump designed for maximum water usage

ADDITIONAL INSTALLED OPTIONS & ACCESSORIES



Push button electric rewind system



Scotty foam system



LED work light



water level indicator



2.5" inlet w/cap and optional valve



Silvex Plus or Phos Chek foam



copolymer polypropylene hose tray



Bubble Cup nozzle
1" 10/24 gpm



Tip 1.5" 20/60 gpm

HIGH PRESSURE/MEDIUM VOLUME PUMP

- 4087-100032..... HONDA HIGH PRESSURE 4 stage
- 3266-HHP24-H..... HONDA HIGH PRESSURE

HIGH VOLUME/MEDIUM PRESSURE PUMP

- 4087-100067..... HONDA MID-RANGE 2-STAGE
- 3266-HAL30024H..... HONDA HIGH VOLUME (HALE)
- 3266-DAR24H..... HONDA HIGH VOLUME (DARLEY)
- OTHER: PLEASE SPECIFY _____

VALVE OPTIONS AND UPGRADES:

- 1025- Upgrade to all... AKRON SWING-OUT BRASS BALL VALVES
- 1430- Upgrade to all... ELKHART BRASS BALL VALVE
- 1430- _____ GATED INLET, ELKHART
- 1025- _____ GATED INLET, AKRON
- 3429-826V6B3P21..... GATED INLET, 2.5" -3 PIECE STAINLESS VALVE
- 3266-SS15FPMNB..... Additional 1.5" DISCHARGE WITH VALVE

OPTIONAL ACCESSORIES & UPGRADES:

- 4000-TI I250..... 250 GALLON COPOLY TANK _____ foam cell
- 4000-T-H200..... 200 GALLON COPOLY TANK _____ foam cell
- 4000-T-H300..... 300 GALLON COPOLY TANK _____ foam cell
- 4000-T-H400..... 400 GALLON COPOLY TANK _____ foam cell
- 4000-T-H500..... 500 GALLON COPOLY TANK _____ foam cell
- 2904-EF32-23-24..... ELECTRIC REWIND ON REEL
- 2904-FH3..... ROLLER & SPOOL ASSEMBLY ON REEL: [] top [] bottom
- 1111-32..... NO HOSE REEL
- 2930-575..... ADDITIONAL 50' OF 1" BOOSTER HOSE
- 2118-BLCHY..... Lightweight, easy handling lead-in booster hose, 12.5'
- 2118-BLCHY..... Lightweight, easy handling lead-in booster hose 25'
- 1111-33..... NO STANDARD 100' BOOSTER HOSE
- 4000-CPPHT..... COPOLY HOSE TROUGH for 1.5" hose : 48" L x 11" W x 8" H
- 2045-EM-4547250..... MC 4 LIGHT GAUGE
- 1242-S106-1600..... FOAM PRO SYSTEM, INSTALLED *with integrated 10 gal foam cell*
- 3306-4072-H/cell..... SCOTTY FOAM SYSTEM INSTALLED *with integrated 10 gal foam cell*
- 3306-4074-H/pickup SCOTTY FOAM SYSTEM INSTALLED
with pick up tube and threaded cap for departments supplied foam pails.
- 2803-FLX2112110..... TRIDENT FOAMATE CLASS A FOAM SYSTEM INSTALLED
with integrated 10 gal foam cell
- 1111-25..... DIAMOND PLATE HOLDER FOR (2) 5 GAL FOAM PAILS
- 1111-INSTALL..... INSTALL MASTER SWITCH, UNIT, AND WIRE
- 4109-H71030401..... LED WORK LIGHT
- 4087-250238..... 12 VOLT ELECTRIC PISTON PRIMER INSTALLED
- 4087-600006..... PUMP END REPLACEMENT KIT (4-STAGE) HOT SHOT 4
- 4087-600007..... PUMP END REPLACEMENT KIT (MIDRANGE) HELLCAT X2
- _____
- _____
- _____
- _____

Remarks: _____

TOTAL: \$ _____

Date: _____ Salesman: _____
 Fire Dept: _____
 Contact: _____
 Phone #: _____
 Fax #: _____
 Email: _____

CUSTOMER REQUIRED TO HAVE FORKLIFT AVAILABLE FOR UNLOADING. *FOR UNITS OVER 7', EXTENDED FORKLIFT REQUIRED